

DeZURIK G-SERIES MANUAL GEAR ACTUATOR SIZING

BHP High Performance Butterfly Valves Handwheel & Chainwheel Actuators

ASME Class 150 (PN 10/16) PTFE (TT, TI, RT, RI) Seat

Valve Size	Actuator Code Handwheel	Shutoff Pressure psi (kPa)	Actuator Code Chainwheel	Shutoff Pressure psi (kPa)
20" 500mm	GS-12A-HD20	<u>285</u> 1960	GS-12A-CW20	<u>285</u> 1960
24" 600mm	GS-12-HD16	<u>285</u> 1960	GS-12-CW20	<u>285</u> 1960
28-30" 700-750mm	GS-12-HD30*	<u>285</u> 1960	GS-12-CW30*	<u>285</u> 1960
36" 900mm	GS-12-HD30*	<u>150</u> 1030	GS-12-CW30*	<u>150</u> 1030

* GS-12-HD30/CW30 is available only in standard and 180° mounting positions

ASME Class 300 (PN 25/40) PTFE (TT, TI, RT, RI) Seat

Valve Size	Actuator Code Handwheel	Shutoff Pressure psi (kPa)	Actuator Code Chainwheel	Shutoff Pressure psi (kPa)
24" 600mm	GS-12-HD24*	<u>740</u> 5090	GS-12-CW20	<u>740</u> 5090

* GS-12-HD24 is available only in standard and 180° mounting positions

ASME Class 150 (PN 10/16) Metal (S2) Seat Dual Seat (TTS2, TIS2 or RTS2, RIS2) Fyre-Block (TTS2 & FB or RTS2 & FB)

Valve Size	Actuator Code Handwheel	Shutoff Pressure psi (kPa)	Actuator Code Chainwheel	Shutoff Pressure psi (kPa)
24" 600mm	GS-12-HD24*	<u>285</u> 1960	GS-12-CW20	<u>285</u> 1960
28-30" 700-750mm	GS-12-HD20	<u>150</u> 1030	GS-12-CW20	<u>285</u> 1960

* GS-12-HD24 is available only in standard and 180° mounting positions

ASME Class 300 (PN 25/40) Metal (S2) Seat Dual Seat (TTS2, TIS2 or RTS2, RIS2) Fyre-Block (TTS2 & FB or RTS2 & FB)

Valve Size	Actuator Code Handwheel	Shutoff Pressure psi (kPa)	Actuator Code Chainwheel	Shutoff Pressure psi (kPa)
14-16" 350-400mm	GS-12-HD24*	<u>285</u> 1960	GS-12-CW20	<u>285</u> 1960
18" 450mm	GS-12-HD30*	<u>150</u> 1030	GS-12-CW30	<u>285</u> 1960

* GS-12-HD24/HD30 is available only in standard and 180° mounting positions

BAW AWWA Butterfly Valves

Handwheel

40 Pound Rim Pull - Class 150B & 250B

Valve Size	Non-Buried Actuator Code	Shutoff Pressure psi (kPa)	Buried Actuator Code
3-8" 80-200mm	GS-6B-HD8*	<u>250</u> 1720	GB-6B-HD8*
10" 250mm	GS-6B-HD8*	<u>150</u> 1030	GB-6B-HD8*
	GS-6B-HD12**	<u>250</u> 1720	GB-6B-HD12**
12" 300mm	GS-6B-HD12**	<u>150</u> 1030	GB-6B-HD12**
	GS-6B-HD16**	<u>250</u> 1720	GB-6B-HD16**
14" 350mm	GS-6B-HD16**	<u>250</u> 1720	GB-6B-HD16**
16" 400mm	GS-6B-HD24**	<u>250</u> 1720	GB-6B-HD24**
18" 450mm	GS-6B-HD24**	<u>150</u> 1030	GB-6B-HD24**
	GS-12A-HD20**	<u>250</u> 1720	GB-12A-HD20**
20" 500mm	GS-12A-HD20**	<u>150</u> 1030	GB-12A-HD20**
	GS-12A-HD30**	<u>250</u> 1720	GB-12A-HD30**
24" 600mm	GS-12A-HD20**	<u>25</u> 170	GB-12A-HD20**
	GS-12A-HD30**	<u>75</u> 515	GB-12A-HD30**
28-30" 700-750mm	GS-12A-HD30**	<u>25</u> 170	GB-12A-HD30**

Handwheel

80 Pound Rim Pull - Class 150B & 250B

Valve Size	Non-Buried Actuator Code	Shutoff Pressure psi (kPa)	Buried Actuator Code
3-12" 80-300mm	GS-6B-HD8*	<u>250</u> 1720	GB-6B-HD8*
14" 350mm	GS-6B-HD12	<u>150</u> 1030	GB-6B-HD12
	GS-6B-HD16**	<u>250</u> 1720	GB-6B-HD16**
16" 400mm	GS-6B-HD16**	<u>250</u> 1720	GB-6B-HD16**
18" 450mm	GS-6B-HD24**	<u>250</u> 1720	GB-6B-HD24**
20" 500mm	GS-6B-HD24**	<u>200</u> 1380	GB-6B-HD24**
	GS-12A-HD20**	<u>250</u> 1720	GB-12A-HD20**
24" 600mm	GS-12A-HD12	<u>25</u> 170	GB-12A-HD12
	GS-12A-HD16	<u>75</u> 5145	GB-12A-HD16
	GS-12A-HD20**	<u>150</u> 1030	GB-12A-HD20**
	GS-12A-HD24**	<u>200</u> 1380	GB-12A-HD24**
	GS-12A-HD30**	<u>250</u> 1720	GB-12A-HD30**
28-30" 700-750mm	GS-12A-HD20	<u>25</u> 170	GB-12A-HD20
	GS-12A-HD30**	<u>75</u> 5145	GB-12A-HD30**
	GS-12A-HD36**	<u>150</u> 1030	GB-12A-HD36**

Chainwheel

40 Pound Rim Pull - Class 150B & 250B

Valve Size	Non-Buried Actuator Code	Shutoff Pressure psi (kPa)
3-8" 80-200mm	GS-6B-CW8*	<u>250</u> 1720
10" 250mm	GS-6B-CW8*	<u>150</u> 1030
	GS-6B-CW12**	<u>250</u> 1720
12" 300mm	GS-6B-CW12**	<u>150</u> 1030
	GS-6B-CW20**	<u>250</u> 1720
14" 350mm	GS-6B-CW20**	<u>250</u> 1720
16" 400mm	GS-6B-CW24**	<u>250</u> 1720
18" 450mm	GS-6B-CW24**	<u>150</u> 1030
	GS-12A-CW20**	<u>250</u> 1720
20" 500mm	GS-12A-CW20**	<u>150</u> 1030
	GS-12A-CW30**	<u>250</u> 1720
24" 600mm	GS-12A-CW20**	<u>25</u> 170

Chainwheel

80 Pound Rim Pull - Class 150B & 250B

Valve Size	Non-Buried Actuator Code	Shutoff Pressure psi (kPa)
3-12" 80-300mm	GS-6B-CW8*	<u>250</u> 1720
14" 350mm	GS-6B-CW12	<u>150</u> 1030
	GS-6B-CW20**	<u>250</u> 1720
16" 400mm	GS-6B-CW20**	<u>250</u> 1720
18" 450mm	GS-6B-CW24**	<u>250</u> 1720
20" 500mm	GS-6B-CW24**	<u>200</u> 1380
24" 600mm	GS-12ACW20**	<u>150</u> 1030
	GS-12A-CW30**	<u>250</u> 1720
28-30" 700-750mm	GS-12A-CW30**	<u>75</u> 515

* If FSDIR or FSDIU is required use HD12 in place of HD8

** Standard or 180° mounting position only without ENK

BOS Uninterrupted Seat Resilient Seated Butterfly Valves

Non-Buried Handwheel

Valve Size	Actuator Code	Shutoff Pressure psi (kPa)
24" 600mm	GS-12-HD12	<u>50</u> 340
	GS-12-HD16	<u>100</u> 690
	GS-12-HD20	<u>125</u> 860
	GS-12-HD24	<u>150</u> 1030
	GS-12-HD30	<u>175</u> 1210
28" 700mm	GS-12-HD30	<u>175</u> 1210
30" 750mm	GS-12-HD16	<u>25</u> 170
	GS-12-HD20	<u>50</u> 340
	GS-12-HD24	<u>75</u> 520
	GS-12-HD30	<u>125</u> 860
32" 800mm	GS-12-HD30	<u>50</u> 340
36" 900mm	GS-12-HD24	<u>25</u> 170
	GS-12-HD30	<u>50</u> 340

Buried/Submerged Handwheel

Valve Size	Actuator Code	Shutoff Pressure psi (kPa)
24" 600mm	GB-12-HD12	<u>50</u> 340
	GB-12-HD16	<u>100</u> 690
	GB-12-HD20	<u>125</u> 860
	GB-12-HD24	<u>150</u> 1030
	GB-12-HD30	<u>175</u> 1210
30" 750mm	GB-12-HD16	<u>25</u> 170
	GB-12-HD20	<u>50</u> 340
	GB-12-HD24	<u>75</u> 520
	GB-12-HD30	<u>125</u> 860
36" 900mm	GB-12-HD24	<u>25</u> 170
	GB-12-HD30	<u>50</u> 340

Non-Buried Chainwheel

Valve Size	Actuator Code	Shutoff Pressure psi (kPa)
24" 600mm	GS-12-CW12	<u>50</u> 340
	GS-12-CW20	<u>125</u> 860
	GS-12-CW30	<u>175</u> 1210
28" 700mm	GS-12-CW30	<u>175</u> 1210
30" 750mm	GS-12-CW20	<u>50</u> 340
	GS-12-CW30	<u>125</u> 860
36" 900mm	GS-12-CW30	<u>50</u> 340

Additional Products

- PEC Eccentric Plug Valves (See Bulletin 12.00-1D For Handwheel/Chainwheel Sizing)
- PEF 100% Port Eccentric Plug Valves (See Bulletin 12.60-1B For Handwheel/Chainwheel Sizing)
- PTW/PFW 3-Way & 4-Way Plug Valves (See Bulletin 20.00-1 For Single/Double Handwheel/Chainwheel Sizing)

Sales and Service

For information about our worldwide locations, approvals, certifications and local representative:

Web Site: DeZURIK.com **E-Mail:** info@DeZURIK.com



250 Riverside Ave. N. Sartell, Minnesota 56377 • Phone: 320-259-2000 • Fax: 320-259-2227

DeZURIK, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing by DeZURIK, Inc. Certified drawings are available upon request.